

USB 2.0 ISDB-T Dongle



Major Features:

- USB2.0 mini-size TV tuners receiver
- Watch and Record TV in Windows on your PC
- 1-segment ISDB-T digital terrestrial tuner receptions
- BML data broadcasting browser supports
- Windows Vista™ compatible
- Stereo Broadcast audio with two national languages
- Sub-title displaying
- High sensitivity telescopic antenna for outdoor reception
- Time-shifting playback, simultaneously watch and record the TV program with immediate rep lay and pause
- *Support EPG (Electronic Program Guide) and schedule recording

** EPG feature depends on television broadcast used in different regions

Specifications:

Bus Interface	USB2.0 (USB1.1 backward compatible)	
TV Tuner	TV Standards	Digital broadcasting for Brazil (ISDB-T)
	Receiving Frequency	1-segment UHF 13 - 69
	TV Audio	Stereo / two national languages
Audio/Video	Video	H.264 (MPEG4-AVC)
	Image Resolution	320x240 (Depend on the content of the broadcasting)
	Video Bit Rate	416kbps (Depend on the content of the broadcasting)
	Audio	MPEG-2 AAC
Dimension	PCB + housing	68 (L) x 24 (W) x 11 (H) mm

System Requirements:

In order to install and use PD260 successfully, your system must satisfy with following requirements.

- **CPU:** Pentium ® 4 2.4GHz CPU or higher
- **OS:** Microsoft® Windows® XP with latest Service Pack or Microsoft® Windows® Vista
- **System memory:** 512MB
- **Disk space:** 1GB for driver and application /25M~30MB per minute for recording the video
- **Graphic card :** 1024x768, DirectX® 9.0c compatible graphic card
- **Sound card :** AC97 compatible PCI sound card
- **CD or DVD ROM:** For Installing the driver and application
- **Interface:** one available USB port



TEL: +886 2 86984245 FAX: +886 2 86984108
Add: 15F, No.81,Sec.1, Hsin Tai Wu Rd.,Hsi -Chih 221, Taipei Hsien, Taiwan
